



Product data	
Product code	MSKA62 Series Cat. N° 500100
Product name	MSKA connector 1xAl/Cu 16-95mm <sup>2</sup>
Wires	1xAl/Cu 16-95mm <sup>2</sup>
Technical data	
Nominal current (IEC)	<b>245</b> A
Nominal voltage (IEC)	<b>750</b> V
Number of poles	<b>1</b> pcs
Max. Cross section	<b>95</b> mm <sup>2</sup>
Tightening torque	<b>20</b> Nm
Inbus key	<b>5</b>
Max. Operating temperature	<b>95</b> °C
IP protection	<b>IP 20</b>
Weight kg/pcs.	<b>9,0</b> kg.
Standards	EN 61238-1 ,SRPS N.F 106, EN 60947-1-7
Material	Flame retardant polyamide UL 94 V-0
Color	Grey-500107/Blue-500108/Yellow-Green-500109
Mounting/connection	DIN rail mounting



MSKA 62.1

### Description

Marel Universal Terminal Class A 16-95mm<sup>2</sup> is intended for connection of aluminum or copper conductors, both solid and stranded - round or sector and of cross section from 16 mm<sup>2</sup> up to 95 mm<sup>2</sup>. They find application in a wide range of power distribution facilities, industrial and infrastructural facilities.

### Drawing

